


code	Watt/max	Volt	Energy class
8031414865376	40W	230V	<b>A+</b>

 Misure - size  
 dimensioni in mm - size mm

**LED-PANEL-30X120-BIS**


<b>Materiale</b>	Alluminio, diffusore in acrilico
<b>Material</b>	Aluminium, acrylic diffuser
<b>Colore</b>	Bianco
<b>Colour</b>	White
<b>Sorgente luminosa</b>	LED SMD 40W
<b>Light source</b>	LED SMD 40W
<b>Driver</b>	Incluso
	Included
<b>Watt/max</b>	40W (PF 0,90)
<b>Codice ean</b>	8031414865376
<b>Ean Code</b>	8031414865376
<b>Temperatura colore</b>	4000K
<b>Colour temperature</b>	4000K
<b>Flusso luminoso</b>	4000 Lm ( 2000 + 2000 )
<b>Luminous flux</b>	4000 Lm ( 2000 + 2000 )
<b>Durata</b>	15.000h
<b>Lifetime</b>	15.000h
<b>on/off</b>	>7500 on/off
<b>Angolo di luce</b>	110° + 110°
<b>Beam angle</b>	110° + 110°
<b>CRI</b>	>80
<b>Grado IK</b>	\
<b>IK degree</b>	\

<b>Classe energetica</b>		
<b>Energy class</b>		
<b>Classe isolamento</b>	II	
<b>Insulation class</b>	II	
<b>Grado IP</b>	IP20	
<b>IP degree</b>	IP20	
<b>Accessori inclusi</b>	\	
<b>Included accessories</b>	\	
<b>Tipo di connessione</b>	connessione con driver classe II	
<b>Connection info</b>	driver connection II insulat. class	
<b>Tipo di packaging</b>	BOX B/W	
<b>Packaging info</b>	BOX B/W	
<b>Altezza inner-box</b>	2,8	
<b>Height inner-box</b>	2,8	
<b>Larghezza inner-box</b>	122,5	
<b>Width inner-box</b>	122,5	
<b>Profondità inner-box</b>	36,5	
<b>Depth inner-box</b>	36,5	
<b>Peso inner-box</b>	2,5	
<b>Weight inner-box</b>	2,5	
<b>Pezzi nell'inner-box</b>	1 pz	
<b>Pcs in inner-box</b>	1 pz	
<b>informazioni</b>	H MASTER-BOX (cm)	35,5
<b>Master-box</b>	LARGHEZZA MASTER-BOX (cm)	129,5
	Pr. MASTER-BOX (cm)	21,5
<b>Master-box info</b>	PESO MASTER-BOX	12,5
	SINGLE BOX IN MASTER	5 pz