



30,000 h | 175-290V~ 50-60Hz | 0.50 | 320° | Ra ≥ 80 | SDCM < 6 | < 0,5s starting time | Warm-up Time < 0,5s | On/Off cycles > 15,000 (1' on / 3' off) | AT 6000h LLMF > 0.90 LSF > 0.90 | Hg Free | Pb Free | FREE | CE

Ordercode	Base	Power	CCT	luminous flux	cover	EAN13	Laser Optical Reading
HPFL-2706C	E27	6W	3000K	800lm	clear glass	8059617678906	
HPFL-2706D	E27	6W	4200K	820lm	clear glass	8059617678913	
HPFL-2706F	E27	6W	6400K	820lm	clear glass	8059617678920	
HPFL-2706SC	E27	6W	3000K	800lm	opal glass	8033638770191	
HPFL-2706SD	E27	6W	4200K	820lm	opal glass	8033638770238	
HPFL-2706SF	E27	6W	6400K	820lm	opal glass	8033638770269	

Inner Box \_ 10 pcs



EAN13	Laser Optical Reading
HPFL-2706C 8033638774984	
HPFL-2706D 8033638774991	
HPFL-2706F 8033638774977	
HPFL-2706SC 8033638779316	
HPFL-2706SD 8033638779323	
HPFL-2706SF 8033638776988	

Outer Box \_ 50 pcs



EAN13	Laser Optical Reading
HPFL-2706C 8033638774960	
HPFL-2706D 8033638774946	
HPFL-2706F 8033638776919	
HPFL-2706SC 8033638771631	
HPFL-2706SD 8033638771648	
HPFL-2706SF 8033638771655	

L.33cm \_ H.14cm \_ P.67cm - Kg 4