



30.000 h
175-250V~ 50-60Hz
λ 0.50
320°
Ra ≥80
SDCM < 6
<0,5s starting time
Warm-up Time <0,5s
On/Off > 15,000 (1 on / 3 off)
AT 6000h LLMF ≥ 0.90 LSF ≥ 0.90
Free Hg
Free Pb
FREE UV
CE

Ordercode	Base	Power	CCT	luminous flux	cover	EAN13	Laser Optical Reading
HPFL-2710C	E27	10W	3000K	1000lm	clear glass	8033638770276	
HPFL-2710D	E27	10W	4200K	1200lm	clear glass	8033638770290	
HPFL-2710F	E27	10W	6400K	1200lm	clear glass	8033638770320	
HPFL-2710SC	E27	10W	3000K	100lm	opal glass	8033638770337	
HPFL-2710SD	E27	10W	4200K	1200lm	opal glass	8033638770382	
HPFL-2710SF	E27	10W	6400K	1200lm	opal glass	8033638770399	

Inner Box _ 10 pcs



EAN13	Laser Optical Reading
HPFL-2710C 8033638777008	
HPFL-2710D 8033638777015	
HPFL-2710F 8033638777022	
HPFL-2710SC 8033638777039	
HPFL-2710SD 8033638774052	
HPFL-2710SF 8033638774069	

Outer Box _ 50 pcs



EAN13	Laser Optical Reading
HPFL-2710C 8033638778364	
HPFL-2710D 8033638778326	
HPFL-2710F 8033638778333	
HPFL-2710SC 8033638778364	
HPFL-2710SD 8033638778371	
HPFL-2710SF 8033638778340	

L.33cm _ H.14cm _ P.67cm - Kg 4