

RAINBOW

Faretto da incasso in alluminio in bianco o cromato.
Recessed aluminum spotlight in white or chromed.



Materiale
alluminio

Colore
bianco
cromo



Temperatura colore
RGB + 4000K



Driver
DC 12V
tensione costante
non incluso

Material
aluminum

Colour
white
chrome



Colour temperature
RGB + 4000K



Driver
DC 12V
constant voltage
not included



EASY DOMOTICA




INC-RAINBOW-M BCO
8031414862627
lumen 110 lm





INC-RAINBOW-M
8031414862603
lumen 110 lm

watt 5W
beam angle 120°
Ø 90 mm



Sistema di connessione / Connection system
Driver pag. 843-852
Controller pag. 854-857



INC-RAINBOW 4000K

ZENIT

Faretto da incasso orientabile con struttura in policarbonato e finitura in nickel, bianco satinato, cromo o oro.
Adjustable recessed spotlight with polycarbonate structure and nickel, satin white, chrome or gold finish.



Materiale
policarbonato

Colore
bianco satinato
nikel
cromo
oro



Temperatura colore
3000K



Driver
integrato

Material
polycarbonate

Colour
satin white
nikel
chrome
gold finish




Colour temperature
3000K



Driver
built-in




INC-ZENIT-SW BCO
8031439881276
lumen 390 lm



INC-ZENIT-SW NIK
8031439901271
lumen 390 lm

INC-ZENIT-SW CR
8031439891275
lumen 390 lm

INC-ZENIT-SW ORO
8031439911270
lumen 390 lm



INC-ZENIT SW

watt 5W
beam angle 120°
Ø 65 mm

