


TUBEX

Incasso in gesso componibile da integrare nel cartongesso per dare omogeneità tra parete e corpo illuminante. Punto luce regolabile e orientabile con finitura in bianco o nero goffrato. Recessed paintable gypsum downlight to be integrated into the plasterboard to give homogeneity between the ceiling and the lighting body. Adjustable light point with embossed black or white finish.



Materiale
gesso e alluminio

Colore

bianco goffrato
nero goffrato



Temperatura colore
3000K / 4000K



Driver
incluso

Material
gypsum and aluminum

Colour
embossed white
embossed black



Colour temperature
3000K / 4000K



Driver
included



technical information **TUBEX**



INC-TUBEX-2C-BCO
8031414883752
lumen

colour temp.	colour
190 lm	



INC-TUBEX-2M-BCO
8031414883769
lumen


colour temp.	colour
190 lm	

INC-TUBEX-2C-NER
8031414883776
lumen

colour temp.	colour
190 lm	



INC-TUBEX-2M-NER
8031414883783
lumen

colour temp.	colour
190 lm	




INC-TUBEX-BASE
8031414883745

watt	2.5W
beam angle	30°
	165 x 165 mm



Modular system:
INC-TUBEX-BASE
+ INC-TUBEX-2



Staffa regolabile /
Adjustable bracket