


XANTO-RF

Incasso in alluminio pressofuso antiriflesso con cavo easy connection integrato.
Diecast aluminum anti-glare down-light with built-in easy domotic cable.



Materiale
alluminio pressofuso

Colore
bianco

Temperatura colore
RGB + 4000K



Driver

DC 24V non incluso
Tensione costante
connessione
in parallelo

Durata e on/off

25.000h
>15.000 on/off

Material

die cast aluminum

Colour

white

Colour temperature
RGB + 4000K



Driver

DC 24V not included
Constant voltage
parallel connecting
system

Life time and on/off


25.000 h
>15.000 on/off



Driver p. 843-852
Controller p. 854-857




INC-XANTO-R120-24V
8031414877942
lumen




1120 lm

watt 12W
beam angle 120°
pf -

Ø 120 mm




INC-XANTO-R220-24V
8031414878697
lumen




3000 lm

watt 30W
beam angle 120°
pf 0.90


Ø 220 mm



Fotometria del prodotto /
Photometric curve



INC-XANTO-R120-24V



INC-XANTO-R220-24V

PANEL

Pannello LED con struttura in alluminio diffusore
in acrilico con cavo easy connection integrato.
LED panel with aluminum structure and acrylic
diffuser with built-in easy domotic cable.



Materiale
alluminio
diffusore in acrilico

Colore
bianco

Temperatura colore
RGB + 4000K



Driver

DC24V
tensione costante
non incluso

Durata e on/off

20.000h
>10.000 on/off

Material

aluminum
acrylic diffuser

Colour

white

Colour temperature
RGB + 4000K



Driver

DC24V
constant voltage
not included

Life time and on/off


20.000h
>10.000 on/off



Driver p. 843-852
Controller p. 854-857




LED-PANEL-60x60-24V
8031414875313
lumen




3280 lm

watt 30W
beam angle 120°
pf 0.90

590 x 590 mm



Fotometria del prodotto /
Photometric curve



LED-PANEL-60x60-24V