



PAVI-078930




PAVI-1216030

NEW
CALPESTABILE
PAVI

IP67 - 1-2-4 LIGHT


1 W



SOURCE		OUTPUT			
1 W	120 lm	80 lm	3000 K	PAVI-014230	36,00 €
			4000 K	PAVI-014240	

24 V IP67 IK06 24°
 WALKABLE TEMPERED GLASS DIFFUSER ALUMINUM


3 W



SOURCE		OUTPUT			
3 W	300 lm	250 lm	3000 K	PAVI-038930	69,00 €
			4000 K	PAVI-038940	

24 V IP65 IK06 12°
 WALKABLE TEMPERED GLASS DIFFUSER ALUMINUM


6 W



SOURCE		OUTPUT			
6 W	660 lm	330 lm	4000 K	PAVI-058940 NEW	76,00 €

24 V IP67 IK06 15°
 WALKABLE TEMPERED GLASS DIFFUSER ALUMINUM

12 W



SOURCE		OUTPUT			
12 W	1.150 lm	840 lm	3000 K	PAVI-1216030	130,00 €
			4000 K	PAVI-1216040	

24 V IP65 IK08 10°
 WALKABLE TEMPERED GLASS DIFFUSER ALUMINUM

Incasso tondo calpestabile per installazione a pavimento. Anello e corpo in alluminio, vetro temperato, cavo in neoprene. Resistenza a pressione di 500 Kg.

Walkable round recessed light for floor installation. Aluminum ring and body, tempered glass, neoprene cable. Pressure resistance of 500 Kg.

INCLUDED



CONTROCASSA IN POLICARBONATO
POLYCARBONATE CASING

OPTIONAL PAG. 269

ALIMENTATORI E CONNETTORI
POWER SUPPLIES AND CONNECTORS

TECHNICAL INDOOR

INDOOR

INDUSTRIAL

TECHNICAL OUTDOOR

OUTDOOR

SOLAR

WORK

SORGENTI